

01/30/98

U.S. P.

PATENT
DOCKET: MMED01

EXPRESS MAIL: *EI 03386926745*

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner of Patents and Trademarks
Box Patent Application
Washington, D.C. 20231

NEW APPLICATION COVER SHEET

Transmitted herewith for filing is the patent application of:

INVENTORS: Norman J. LeMaire III and William R. Hanna, Jr.

FOR: Surgical Instrument with Offset Jaw Actuator

TYPE OF APPLICATION

XX Original

 Design

 Plant

PAPERS ENCLOSED WHICH ARE REQUIRED FOR FILING DATE UNDER 37 CFR
1.53(B)(Regular) OR 37 CFR 1.53(Design) APPLICATION

13 Page(s) of specification

6 Page(s) of claims

1 Page(s) of abstract

12 Sheet(s) of drawings *Pgs 1-20*

 Formal

XX Informal

ADDITIONAL PAPERS ENCLOSED

 Preliminary Amendment

XX Information Disclosure Statement (37 CFR 1.98)

XX Form PTO-1449

XX Citations

 Assignment of Invention to: _____

 Declaration of Biological Deposit

XX Declaration and Power of Attorney

XX A verified statement to establish small entity status
under 37 CFR 1.9 and 37 CFR 1.27.

Certification Under 37 CFR 1.10

I hereby certify that this New Application Cover Sheet and the documents referred to as
enclosed therein are being deposited with the United States Postal Service on this date
1/31/98 in an envelope as "Express Mail Post Office to Addressee" Mailing Label
Number EI 03386926745 addressed to the: Commissioner of Patents and Trademarks,
Box Patent Application, Washington, D.C. 20231.

Ronald R. Kilporen
Type/Print name of person mailing
Ronald R. Kilporen
Signature of person mailing

Other _____
The filing fee has been calculated as below:

XX Regular Application

For:	No. filed	No.Extra	Rate	Small Entity	Rate	Other than Small Entity
Basic Filing Fee				\$395		\$790
Total Claims	<u>21</u> -20=	<u>1</u>	x\$11	<u>11</u>	x\$22	
Independent Claims	<u>3</u> -3=	<u>0</u>	x\$41		x\$82	
Multiple Dependent Claims			\$135		\$270	
Total:				<u>\$406 -</u>		

Design Application Filing fee calculation _____
Plant Application Filing fee calculation _____

XX A check No: 1541 in the amount of \$406 - to cover the filing fee.
(Please refund any overpayment.)

Please charge the Deposit Account No. _____ in the amount of _____.

The commissioner is hereby authorized to charge payment of the following fees associated with this communication to credit any overpayment to Deposit Account No. _____

Any additional fees required under 37 CFR 1.16

Any patent application processing fees under 37 CFR 1.17


The commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. _____

Any patent application processing fees under 37 CFR 1.17.

Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Date: 1/31/98

Reg. No. 37,656


Ronald R. Kilponen
65 Plymouth Road
Bellingham, MA.
02019-1242

Phone: 508/966-4137

To the Commissioner of Patents and Trademarks:

5 Your petitioners, Norman J. LeMaire III, a citizen of the United
States, and residing at 595 Pleasant Street, Raynham, MA. 02767 and William
R. Hanna Jr., a citizen of the United States and residing at 5500 N. Main
Street, Bldg. 15 Apt. 209, Fall River, MA. 02720 pray that Letters Patent
be issued to them for the invention entitled, Surgical Instrument with
Offset Jaw Actuator, of which the following is a specification.

10

RECEIVED

TITLE: Surgical Instrument with Offset Jaw Actuator

FIELD:

5 The present version of this invention relates generally to the field of surgical instruments utilized primarily in non-invasive surgery. Other uses of the principles of this instrument may find application in industries or professions requiring the use of grasping or cutting tools.

BACKGROUND:

10 Surgical punches and graspers have been known in the art for some time. They generally involve a fixed or stationary member, an actuator extending from an actuator handle to the working end of the stationary member where the actuator engages a jaw member.

15 Actuation of the actuator causes the jaw member to pivot and open relative to the stationary member where tissue is inserted between the jaw member and the portion of the stationary member. The handle is then operated to close the jaw member relative to the stationary member where the engaged tissue is lacerated or grasped and can then be removed.

20 This type of operation is well known in the art and various types of surgical instruments have been developed. This process however puts large stresses on the components of the instruments due to the high forces needed to lacerate or grasp and remove some tissue. These high stresses cause premature failure of the instruments from wear or worse yet catastrophic failure of the components while in use, resulting in metal fragments or
25 slivers being dispersed in the operative site. The metal fragments are often difficult to locate and remove causing unnecessary complications, increased medical time and greater possibility of less than optimum patient results. If metal fragments or slivers remain from catastrophic instrument failure and are not located and removed after the failure, a second
30 procedure may be necessary to remove the metal fragments or slivers and to

correct or rectify any tissue damage that may have occurred.

5 A typical failure mode in the prior art occurred when the pin
attaching the jaw member to the stationary member or the pin attaching the
actuator to the jaw member failed. Other failures occurred when the
actuator bar was forced such that the bar bent, essentially locking the
instrument. A jammed actuator bar would sometimes fail with the jaw member
in a fully opened position and this would then cause damage to the
operative site when removing the instrument with the jaw locked open.
10 Another typical failure occurred when closing the jaw member on a piece of
hard tissue, the actuator bar would fail and buckle upward immediately
before the connection of the actuator bar and the jaw member. This was due
to the necking down of the height and width of the actuator bar. Still
other failures occurred when the contact surfaces between the actuator bar
and the inner tip fractured and jammed the instrument.

15 Several other embodiments have addressed these problems by
eliminating the pins typically used to attach the jaw member to the
actuator and the jaw member to the stationary member. The pins have been
replaced by a lug and groove arrangement. This procedure is costly and
difficult to machine due to the precise dimensions required for smooth non-
binding operation and the small size of the components.
20

25 Several other embodiments have utilized a pin for one of the
attachments, either between the jaw member and actuator or between the jaw
member and stationary member with a lug and groove for the other
attachment. These prior art embodiments still had failures of the lug and
groove surfaces due to high loading and small contact surfaces. These
embodiments have tried to decrease the likelihood of catastrophic failure
or premature failure by increasing the size of the components and
attachments resulting in larger instrument size and more damage to the
operative site from the increased size of the incisions and instruments.
30 Large instrument size also decreases the finesse that can be obtained in

the operation of the instruments in removing only specific tissue, resulting in removal of more tissue than may be necessary and therefore longer healing time and less than optimum patient results and recovery.

Consequently there is a need for an instrument in which the size can be kept at a minimum while the cutting force applied to the components can be kept high resulting in the minimizing of the likelihood of catastrophic failure or premature wear from overloading. The instrument should have a high strength to size ratio and have an optimum design to allow the highest operational forces for the smallest size with the appropriate materials.

SUMMARY

In view of the foregoing disadvantages well known in the prior art there is a need for a surgical instrument with an offset jaw actuator.

A first object of this embodiment of the invention is to provide a relatively easy design to manufacture.

A second object of this embodiment of the invention is to provide an instrument having a small size.

Another object of this embodiment of the invention is to provide an instrument capable of operating with high actuation forces while minimizing the likelihood of instrument failure.

An additional object of this embodiment of the invention is to provide an instrument having both a small size and capable of handling high actuation forces while minimizing the likelihood of instrument failure.

Another object of this embodiment of the invention is to provide an instrument with an increased life expectancy from decreased wear thereby requiring less maintenance and less cost over the lifetime of the instrument.

An additional object of this embodiment of the invention is to provide an instrument having enough strength to decrease the probability of catastrophic failure of components.

Another object of this embodiment of the invention is to provide an instrument capable of use in small work areas.

Another object of this embodiment of the invention is to provide an instrument that is more easily flushed and cleaned following use.

5 These together with other objects of this instrument, along with various features of novelty which characterize this instrument, are pointed out with particularity in the claims annexed hereto and forming a part of this disclosure. For a better understanding of this instrument, its operating advantages and the specific objects attained by its uses,
10 reference should be had to the accompanying drawings and following descriptive matter in which there is illustrated a preferred embodiment of this version of the instrument.

BRIEF DESCRIPTION OF DRAWINGS

5 Fig. 1 shows a side view of the surgical tool with one embodiment of the hand grip.

Fig. 2 shows a side view of the instrument with the inner tip in the open or second position.

Fig. 3 shows a side view of the instrument with the inner tip in the closed or first position.

Fig. 4 shows a detail partial side view of the closed end with the inner tip in the open or second position.

Fig. 5 shows a detail partial side view of the closed end with the inner tip in the closed or first position.

25 Fig. 6 shows a cross section view along longitudinal axis A-A in Fig. 16, of the outer shaft.

Fig. 7 shows a detail partial cross section view along longitudinal axis A-A in Fig. 16, of the closed end of the outer shaft.

Fig. 8 shows a detail partial bottom view of the closed end of the outer shaft.

Fig. 9 shows a detail side view of the inner tip.

Fig. 10 shows a detail partial top view of the connected end of the inner tip.

Fig. 11 shows a detail partial side view of the inner tip.

Fig. 12 shows a side view of the actuator bar.

Fig. 13 shows a detail partial top view of the tip end of the actuator bar.

Fig. 14 shows a detail partial side view of the actuation end of the actuator bar.

Fig. 15 shows a detail partial side view of the tip end of the actuator bar.

Fig. 16 shows a top detail partial view of the closed end of the outer shaft.

Fig. 17 shows a detail partial top view of the closed end of the outer shaft with the inner tip and actuator bar in the closed position.

Fig. 18 shows a detail partial top view of the closed end of the outer shaft with the inner tip and actuator bar in the open position.

Fig. 19 shows an exploded partial view of an alternative embodiment of an instrument utilizing two cuppers working in conjunction with two actuator bars.

Fig. 20 shows a detail partial assembled top view of the dual actuator embodiment of Fig. 19.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the drawings in detail wherein like elements are indicated by like numerals, there is shown in Fig. 1 the surgical tool 27 having a hand grip 48 connected to an outer shaft 50. Fig. 2 shows a view of the instrument 25 in the open position 95, or where the inner tip 100 is in a position farthest away from the outer shaft 50 and the actuator bar 176 actuation end 180 is farthest from the outer shaft 50. Fig. 3 shows the instrument 25 in the closed position 96, where the inner tip 100 is

5 contained primarily within the closed end 54 of outer shaft 50 and the actuator bar 176 actuation end 180 is closest to the outer shaft 50. Other means for translating the actuation bar 176 could include threads, triggers, ratchets, electrical motors and others providing a translational movement to the actuator bar 176. This disclosure is not meant to limit these means only to the hand grip 48 as shown.

The inner tip 100, outer shaft 50, and actuator bar 176 are, in a preferred embodiment, machined from stainless steel. Other materials, both ferrous and non-ferrous could be substituted.

10 The inner tip 100 rotates relative to the outer shaft 50 around the tip axle 56, Fig. 2. The tip axle 56 is inserted through the axle hole 60 of the outer shaft 50, Fig. 6, and the tip hole 106 of the inner tip 100, Fig. 8. An actuator axle 44, Figs 2,3, can be used to restrain the actuator bar 176, to movement in one dimension. The actuator axle 44 is inserted through both sides of the outer shaft 50 through shaft hole 42 and through a slot 170, Fig. 12. The rotation of the inner tip 100 is achieved through the translation of the actuator bar 176 relative to the outer shaft 50 within a trough-like opening 68, Fig. 16.

15 The actuator bar 176 receives translational motion from the rotational movement of the actuator lever 46 relative to the hand grip 48 Fig. 1, or other means for translating the actuator bar 176. The actuator bar 176 engages the inner tip 100 with the tip end 178 via a radial ridge 182 having an upper surface 184 and a lower surface 186 which is wider than the upper surface 184, Figs 13 & 15. A preferred embodiment has a ratio of the surface area of the upper surface 184 to the surface area of the lower surface 186 of less than one. The lower surface 186 has as a maximum dimension corresponding to the width of the actuator bar 176. In other words, in a preferred embodiment, the width of the lower surface 186 is equal to or less than the width of the actuator bar 176.

25 The radial ridge 182 of the actuation bar 176, Fig. 15, engages the

inner tip 100 curved slot 108, Figs. 9,10 which has a first surface 110 corresponding in size to the upper surface 184 and a second surface 112 corresponding in size to the lower surface 186, Figs. 9,10,12. The ratio of the first surface 110 area to the second surface 112 area in a preferred embodiment is less than one. When the actuator end 180 moves away from the outer shaft 50, the upper surface 184 engages the first surface 110, causing the inner tip 100 to rotate around tip axle 56 to the open position 95. when the actuator end 180 moves towards the outer shaft 50, the lower surface 186 engages the second surface 112, causing the inner tip 100 to rotate around tip axle 56 to the closed position 96.

This arrangement provides a maximum surface area and therefore less stress between the inner tip 100 and the actuator bar 176 when the instrument 25 is moved from the open position 95 to the closed position 96, Figs. 1, 2. The actuation of the actuator bar 176 is performed on the actuation end 180 by any actuation means commonly known in the art of which the hand grip 48 is but one embodiment. Other methods for providing translational movement to the actuator bar 176 could be utilized.

This larger surface area for the interface between the inner tip 100 and actuator bar 176 is further provided by the transition 190 of the actuator bar 176, Figs. 13,17 & 18. The transition 190 can be described as a shifting of the longitudinal axis of the actuator bar 176 near the tip end 178. Fig. 17 shows a longitudinal axis 75 and an offset axis 78 where the offset axis 78 is shifted at a transition 190 a predetermined distance 80, Fig. 17. In a preferred embodiment, the offset axis 78 is shifted a distance in the range of 20% - 75% of the width of the actuator. The shifting of the offset axis 78 occurs over a predetermined distance or shift distance 192. In a preferred embodiment, the shift distance 192 occurs over a maximum distance of two times the width 168 of the actuator bar 176. Fig. 13 shows a center 188 of the upper surface 184. Also shown is a transition location 194. This is the location on the length of the

actuator bar 176 where the transition 190 occurs. In a preferred embodiment, the transition location 194 occurs within a maximum of four times the width 168 of the actuator bar 176 from the center 188. While this particular embodiment shows radii in the actuator bar 176 affecting the offset axis 78, other configurations could be utilized to shift the offset axis 78 such as linear transitions, steps and various sized radii.

The use of the transition 190 also allows the actuator bar 176 to maintain a constant width 168 along the entire length of the actuator bar 176. There is no necking down of the width 168 of the actuator bar 176 near the tip end 178.

The transition 190 allows the actuator bar 176 to engage the inner tip 100 in an offset position, this allows a greater potential contact surface interface between the actuator bar 176 and the inner tip 100. This results in larger surface areas of the second surface 112 and the lower surface 186, then could be provided if the actuator bar 176 had no transition 190. The larger surface areas of second surface 112 and lower surface 186 is especially important. Much of the prior art utilizes a connection between a straight actuator which necks down in height and width at the biting tip. The art is limited in the contact surface area that is possible between the components, because the actuator fits within the width of the biting tip.

In addition, the transition 190 allows the radial ridge 182 to engage the curved slot 108 of the inner tip 100 from the open side 114. This is a significant advantage in that the curved slot 108 with first surface 110 and second surface 112 can be machined from the open side 114 of the inner tip 100. The machining of curved slot 108 from the open side 114 provides an increased cost savings over machining from the connected end 102 as is done in the prior art. The access from the open side 114 decreases the complexity of cutting the curved slot 108. The nature of the relative openness of the curved slot 108 engagement with the radial ridge 182 makes

access for cleaning the instrument 25 easier and safer in that it is easier to brush and penetrate the interface of the actuator bar 176 and the inner tip 100. The access to the open side 114 is greater than the prior art because the curved slot 108 is machined from the side as opposed to the connected end 102.

When the actuator bar 176 engages the inner tip 100 to move from the open position 95 to the closed position 96, this is when the highest force on these components is encountered. In moving from the open position 95 to the closed position 96 the tissue (not shown) that is required to be removed or grasped is between the inner tip 100 biting edge 105 and the outer shaft 50 die edge 58. The highest forces and therefor the highest stresses on the instrument occur at this time and this is when the instrument is most likely to fail, while a piece of very hard tissue is being lacerated or grasped for removal.

Because there is an open side 114 on the tip 100, when the actuator bar 176 is contained within the outer shaft 50 and engaged with the inner tip 100, the actuator bar 176 tip end 178 flat side 174 is adjacent the tip opening 62 actuator edge 64, Fig. 7. While the inner tip 100 first side 116 is adjacent the tip edge 66 and the second side 118 is adjacent the depressed side 172 of the tip end 178, Fig. 13.

The interaction of the actuator bar 176, inner tip 100 and tip opening 62 results in three pair of contact surfaces between the components. In other words, frictional losses occur between flat side 174 and actuator edge 64, first side 116 and tip edge 66, and second side 118 and depressed side 172, best shown Fig. 17. These three pair of contact surfaces are a reduction as compared to the prior art which generally has 4 pair of contact surfaces.

A reduction in contact surfaces results in less potential friction from the operation of the components due to rough surfaces and tolerance build up and also less wear. This reduction in frictional losses means

more of the force applied to the instrument 25 is available for lacerating or grasping action between the biting edge 105 and die edge 58. The instrument 25 is subject to less stress for the same amount of actuation and therefore there is less probability of failure or premature wearing.

5 To summarize, the transition 190 of the actuator bar 176 allows greater contact areas between the components, decreases the cost of machining, increases the accuracy of the machining such that a smoother action of the components occurs, decreases the number of contact surfaces between the components to three as opposed to the four found in the prior art decreasing the likelihood of hidden contaminants and promotes cleaning
10 of the interface between the components.

Operation:

Assuming the instrument 25 begins in the closed position 96, the operator engages the hand grip 48 and rotates the actuator lever 46 away from the hand grip 48. This rotational movement results in a translation of the actuator bar 176 towards the hand grip 48. The inner tip 100 connected end 102 is engaged with the tip end 178 and translation of the actuator bar 176 causes the inner tip 100 to rotate around a tip axle 56 which interconnects the inner tip 100 and outer shaft 50. The inner tip 100 opens to a position between the closed position 96 and the open position 95, Figs. 1 & 2.

The interconnection between the inner tip 100 and the actuator bar 176 occurs between the first surface 100 of curved slot 108 and the upper surface 184 of radial ridge 182.

When the user desires to return the surgical tool 27 to the closed position 96, the actuator lever 46 is rotated towards the hand grip 48 reversing the translation of the actuator bar 176.

The lower surface 186 of the radial ridge 182 engages the second surface 112 of curved slot 108 causing inner tip 100 to rotate about tip

axle 56 relative to the outer shaft 50. The biting edge 105 can then grasp or lacerate tissue or another object between the biting edge 105 and die edge 58.

5 Alternative Embodiment

Figs 19 and 20 show an alternative embodiment of an instrument 25. This embodiment has two actuator bars 225a, 225b which are mirror images of one another contained within a retainer 250. The actuator bars 225a, 225b also have transitions 270a, 270b with second ends 290a, 290b for engagement with cuppers 300a, 300b for grasping, lacerating or cupping another object. While this embodiment and the one described prior, generally show the transitions and offset axis in a single plane generally horizontal, other offset directions could be utilized. This may be particularly useful in the embodiment shown in Figs 19 & 20. In this embodiment, the direction of the offset axis could be vertical either above or below the longitudinal axis, thereby providing for some mechanical advantage to, for example, the cuppers 300a, 300b.

Fig. 20 shows the actuator bars 225a,b having a longitudinal axis 306a,b with transitions 270a,b resulting in offset axis 308a,b where the offset axis 308a,b are offset a distance 310 over a shift distance 312. The distance 310 is in the range of 20% - 70% of the width of the actuator bar 225a,b while the length or shift distance 312 over which this occurs is a maximum of two times the width of the actuator bar 225a,b.

The second ends 290a, 290b have push surfaces 292a, 292b for engagement with cuppers 300a, 300b first surfaces 302a, 302b (not shown) for biasing the cuppers 300a, 300b to the closed position 235, (not shown)

The second end 290a, 290b also have pull surfaces 294a (not shown), 290b for engagement with second surface 304a, 304b (not shown) to bias the cuppers 300a, 300b to an open configuration, Fig. 19.

It will now be apparent to those skilled in the art that other

PATENT
DOCKET: MMED01
EXPRESS MAIL: EI033869267US

embodiments, improvements, details and uses can be made consistent with the letter and spirit of the foregoing disclosure and within the scope of this patent, which is limited only by the following claims, construed in accordance with the patent law, including the doctrine of equivalents.

2025-04-24 14:00:00

CLAIMS

I claim:

1. A tool for lacerating or grasping other objects, the tool comprising:

5 an outer shaft with an open end and a closed end and an opening
located parallel to a longitudinal axis extending from the open
end to near the closed end;

10 an actuator bar with a tip end and an actuation end and a
consistent width, a transition near the tip end resulting in the
tip end having a longitudinal offset axis displaced from the
longitudinal axis in a single plane, the actuation end engaging a
translation means for translation of the actuator bar relative to
the outer shaft, a radial ridge located near the tip end for
5 engagement with an inner tip; and

20 the inner tip rotationally engaged to the outer shaft near the
closed end and the inner tip having a connected end, the inner tip
interengaging the radial ridge with a curved slot located on an
open side where translation of the actuator bar relative to the
outer shaft results in rotation of the inner tip relative to the
outer shaft.

25 2. The tool of claim 1, wherein:

 the translation means is a hand grip.

3. The tool of claim 1, further comprising:

30 the outer shaft having a die edge near the closed end and the

inner tip having a biting edge, the die edge and biting edge for interacting with objects locatable between the biting edge and the die edge.

- 5 4. The tool of claim 1, wherein:

the transition occurs over a shift distance not exceeding two times the width of the actuator bar.

- 10 5. The tool of claim 1, wherein:

the offset axis is displaced from the longitudinal axis a distance of 20% - 75% of the width of the actuator bar.

- 5 6. The tool of claim 1, further comprising:

the radial ridge having an upper surface smaller in area than a lower surface and the curved slot having a first surface smaller in area than a lower surface.

- 20 7. The tool of claim 1, further comprising:

the transition is located in the actuator bar within a transition location of four times the width of the actuator bar from a center.

- 25 8. A tool for interacting with objects, the tool comprising:

an outer shaft with an open end and a closed end and a trough-like opening located parallel to a longitudinal axis extending from the

open end to near the closed end, a shaft hole and an axle hole located perpendicular to the longitudinal axis through the outer shaft;

5 an actuator bar with a tip end and an actuation end with a slot located therebetween and a consistent width, a transition near the tip end resulting in the tip end having a longitudinal offset axis displaced from the longitudinal axis in a single plane, the actuation end engaging a translation means for translation of the
10 actuator bar relative to the outer shaft, a radial ridge located near the tip end for engagement with an inner tip; and

the inner tip rotatably attached to the outer shaft near the closed end by a tip axle through the axle hole, the inner tip having a connected end, the inner tip interengaging the radial
5 ridge with a curved slot located on an open side such that translation of the actuator bar relative to the outer shaft results in rotation of the inner tip relative to the outer shaft.

20 9. the tool of claim 8, wherein:

the offset axis is displaced from the longitudinal axis a distance of 20% - 75% of the width of the actuator bar.

25 10. The tool of claim 8, wherein:

the transition occurs over a shift distance not exceeding two times the width of the actuator bar.

30 11. The tool of claim 8, further comprising:

the transition is located in the actuator bar within a transition location of four times the width of the actuator bar from a center.

5 12. The tool of claim 8, further comprising:

the radial ridge having an upper surface smaller in area than a lower surface and the curved slot having a first surface smaller in area than a lower surface.

10 13. The tool of claim 8, wherein:

the translation means is a hand grip.

15 14. The tool of claim 8, further comprising:

the outer shaft having a die edge near the closed end and the inner tip having a biting edge, the die edge and biting edge for interacting with objects locatable between the biting edge and the die edge.

20 15. A tool for interacting with objects, the tool comprising:

an outer shaft with an open end, a closed end and a trough-like opening located parallel to a longitudinal axis extending from the open end to near the closed end, a shaft hole and an axle hole located perpendicular to the longitudinal axis through the outer shaft, a die edge circumscribing a tip opening near the closed end for interacting with an inner tip;

an actuator bar with a tip end and an actuation end having a slot perpendicular to a longitudinal axis there between, the actuator bar having a consistent width, a transition near the tip end resulting in the tip end having a longitudinal offset axis displaced from the longitudinal axis in a single plane, the actuation end engaging a translation means for translation of the actuator bar relative to the outer shaft in a direction parallel to the longitudinal axis, a radial ridge located near the tip end for engagement with the inner tip; and

the inner tip rotatably attached to the outer shaft near the closed end by a tip axle through the axle hole, the inner tip locatable within a tip opening in a closed position, the inner tip having a connected end opposite a biting end, the inner tip interengaging the radial ridge with a curved slot located on an open side such that translation of the actuator bar relative to the outer shaft results in rotation of the inner tip relative to the outer shaft.

16. The tool of claim 15, further comprising:

the radial ridge having an upper surface smaller in area than a lower surface and the curved slot having a first surface smaller in area than a lower surface.

17. the tool of claim 15, wherein:

the offset axis is displaced from the longitudinal axis a distance of 20% - 75% of the width of the actuator bar.

18. The tool of claim 15, wherein:

the transition occurs over a shift distance not exceeding two times the width of the actuator bar.

5

19. The tool of claim 15, further comprising:

the transition is located in the actuator bar within a transition location of four times the width of the actuator bar from a center.

10

20. The tool of claim 15, wherein:

the translation means is a hand grip.

15

21. The tool of claim 15, further comprising:


the outer shaft having a die edge near the closed end and the inner tip having a biting edge, the die edge and biting edge for interacting with objects locatable between the biting edge and the die edge.

20

ABSTRACT OF THE DISCLOSURE



A tool for grasping or cutting with an offset jaw actuator is shown. The offset provides a consistent width to the actuator discouraging buckling under heavy loading situations. The offset also provides for greater contact area between the actuator and inner tip. The interface of the actuator with the inner tip is machined into the inner tip from the side resulting in an instrument that is easier and cheaper to manufacture and clean while retaining maximum strength for cutting or grasping.

5






Express: EIO 3386926745





0000450000 04 2009



Express: E103386926745






Express: 6103386 926745




Express: ET03386926745

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---



Express: E103386926745


Fig 16



Express: EIO33869267us


00016090 043098

Parameter	Value	Parameter	Value
α_1	0.0000	α_2	0.0000
α_3	0.0000	α_4	0.0000
α_5	0.0000	α_6	0.0000
α_7	0.0000	α_8	0.0000
α_9	0.0000	α_{10}	0.0000
α_{11}	0.0000	α_{12}	0.0000
α_{13}	0.0000	α_{14}	0.0000
α_{15}	0.0000	α_{16}	0.0000
α_{17}	0.0000	α_{18}	0.0000
α_{19}	0.0000	α_{20}	0.0000
α_{21}	0.0000	α_{22}	0.0000
α_{23}	0.0000	α_{24}	0.0000
α_{25}	0.0000	α_{26}	0.0000
α_{27}	0.0000	α_{28}	0.0000
α_{29}	0.0000	α_{30}	0.0000
α_{31}	0.0000	α_{32}	0.0000
α_{33}	0.0000	α_{34}	0.0000
α_{35}	0.0000	α_{36}	0.0000
α_{37}	0.0000	α_{38}	0.0000
α_{39}	0.0000	α_{40}	0.0000
α_{41}	0.0000	α_{42}	0.0000
α_{43}	0.0000	α_{44}	0.0000
α_{45}	0.0000	α_{46}	0.0000
α_{47}	0.0000	α_{48}	0.0000
α_{49}	0.0000	α_{50}	0.0000
α_{51}	0.0000	α_{52}	0.0000
α_{53}	0.0000	α_{54}	0.0000
α_{55}	0.0000	α_{56}	0.0000
α_{57}	0.0000	α_{58}	0.0000
α_{59}	0.0000	α_{60}	0.0000
α_{61}	0.0000	α_{62}	0.0000
α_{63}	0.0000	α_{64}	0.0000
α_{65}	0.0000	α_{66}	0.0000
α_{67}	0.0000	α_{68}	0.0000
α_{69}	0.0000	α_{70}	0.0000
α_{71}	0.0000	α_{72}	0.0000
α_{73}	0.0000	α_{74}	0.0000
α_{75}	0.0000	α_{76}	0.0000
α_{77}	0.0000	α_{78}	0.0000
α_{79}	0.0000	α_{80}	0.0000
α_{81}	0.0000	α_{82}	0.0000
α_{83}	0.0000	α_{84}	0.0000
α_{85}	0.0000	α_{86}	0.0000
α_{87}	0.0000	α_{88}	0.0000
α_{89}	0.0000	α_{90}	0.0000
α_{91}	0.0000	α_{92}	0.0000
α_{93}	0.0000	α_{94}	0.0000
α_{95}	0.0000	α_{96}	0.0000
α_{97}	0.0000	α_{98}	0.0000
α_{99}	0.0000	α_{100}	0.0000

[illegible]

EXPRESS: ETO3386926745

Fig 20



EXPIRES: E103306926745

COMBINED DECLARATION AND POWER OF ATTORNEY

As the below named inventor, I/We hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention which has the following title:

Surgical Instrument with Offset Jaw Actuator

the specification of which:

XX is attached hereto,

_____ was filed on _____ as _____

Application Serial No: _____

and was amended on _____
(if applicable)

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge a duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

PRIORITY CLAIM - SECTION 119

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventors certificate or any PCT International application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

XX no such applications have been filed.

such applications have been filed as follows:

Country: App. Number: Day/Month/Year: Priority Claimed:
 Yes No
 Yes No

PRIORITY CLAIM - SECTION 120

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of

_____ such applications have been filed as follows:

Application Serial No: Filing Date: Patented, Pending, Abandoned:

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, Section 1001, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY

As the named inventor(s), I/We, hereby appoint the following attorney to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. Direct all correspondence and telephone calls to:

Ronald R. Kilponen
65 Plymouth Road
Bellingham, MA.
02019-1242

Telephone: 508/966-4137 Registration No: 37,656

SIGNATURES

Full name of sole or first inventor Norman J. LeMaire III

Inventors Signature

Date 1-29-98 Country of Citizenship United States

Residence 595 Pleasant Street, Raynham, MA. 02767

Post Office Address Same

Full name of second joint inventor William R. Hanna, Jr.

Inventors Signature

Date 1-29-98 Country of Citizenship United States

Residence 5500 N. Main Street, Bldg. 15 Apt 209, Fall River, MA. 02720

Post Office Address Same

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First/Sole Applicant or Patentee: Norman J. LeMaire III
Joint/Second Applicant or Patentee: William R. Hanna, Jr.
Serial or Patent No: _____
Filed or Issued: Herewith
Title: Surgical Instrument with Offset Jaw Actuator

VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS
UNDER 37 CFR 1.9(f) AND 1.27(b) - INDEPENDENT INVENTOR

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the above identified invention described in:

- ☒ the specification filed herewith.
☐ application identified above.
☐ the patent identified above.
☐ the Provisional Patent application filed herewith

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e). Each person concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ no such person, concern, or organization
☐ persons, concerns or organizations listed below

Full Name: _____

Address: _____

☐ Individual ☐ Small business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application for patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Full name of sole/first Inventor Norman J. LeMaire III
Signature of sole/first Inventor *Norman J. LeMaire III*
Date of Signature 1-29-98

Full name of Second/Joint Inventor William R. Hanna, Jr.
Signature of Second/Joint Inventor *William R. Hanna Jr.*
Date of Signature 1-29-98